








ESLINGA DE POLIESTER ESLINGAR 1,5M X 75MM 6TN EN U 3TN EN TIRO DIRECTO
COLOR AMARILLO COEFICIENTE CS6 - 50007422



COLOR	OJAL (mm)	ANCHO (mm)	CARGA DE TRABAJO					CAPAS	CÓDIGO	TIRO DIRECTO	LAZO
			TIRO DIRECTO	LAZO	U	45°	60°				
	300	50	1000	800	2000	1400	1000	1	WXE22050		
	350	60	2000	1600	4000	2800	2000	2	WXE22060		
	400	75	3000	2400	6000	4200	3000	2	WXE22075		
	450	100	4000	3200	8000	5600	4000	2	WXE22100		
	500	125	5000	4000	10000	7000	5000	2	WXE22125		
	500	150	6000	4800	12000	8400	6000	2	WXE22150		

CARACTERISTICAS

- 01.** Fabricado según norma Iram 5378.
Líneas negras para identificación de carga.
- 02.** Patrón internacional de colores.
- 03.** Mejor absorción al golpe y distribución de carga.
Ojales protegidos según especificación.
- 04.** Livianas y fácil de almacenar, no rayan la carga.

DESCRIPCION / UTILIZACION

Eslinga de fibra sintética ojal ojal coeficiente 6.
 Utilizada para izaje y movimientos de carga en general.